



R-T表

广东爱晟电子科技有限公司

R25	10(KΩ)	阻值精度	1.0%	型号: DT103F3743A			
B25/50	3743K	B值精度	1.0%				
Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)	Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)
-40	272.951	285.102	297.763	3	26.2131	26.7396	27.2739
-39	256.260	267.497	279.199	4	25.0026	25.4926	25.9896
-38	240.705	251.101	261.920	5	23.8553	24.3112	24.7735
-37	226.201	235.822	245.828	6	22.7676	23.1918	23.6216
-36	212.670	221.577	230.835	7	21.7360	22.1307	22.5302
-35	200.040	208.290	216.859	8	20.7574	21.1245	21.4959
-34	188.246	195.889	203.823	9	19.8287	20.1700	20.5152
-33	177.227	184.310	191.658	10	18.9471	19.2644	19.5850
-32	166.927	173.494	180.301	11	18.1099	18.4048	18.7026
-31	157.294	163.384	169.693	12	17.3147	17.5886	17.8651
-30	148.282	153.931	159.779	13	16.5591	16.8135	17.0701
-29	139.845	145.087	150.510	14	15.8409	16.0770	16.3151
-28	131.944	136.810	141.840	15	15.1580	15.3772	15.5979
-27	124.542	129.059	133.726	16	14.5086	14.7118	14.9164
-26	117.603	121.798	126.129	17	13.8908	14.0792	14.2687
-25	111.096	114.992	119.014	18	13.3028	13.4773	13.6528
-24	104.991	108.611	112.345	19	12.7431	12.9047	13.0671
-23	99.261	102.626	106.094	20	12.2102	12.3597	12.5098
-22	93.880	97.008	100.230	21	11.7026	11.8408	11.9795
-21	88.826	91.734	94.728	22	11.2191	11.3467	11.4747
-20	84.076	86.780	89.563	23	10.7582	10.8760	10.9940
-19	79.636	82.153	84.740	24	10.3189	10.4275	10.5362
-18	75.458	77.800	80.207	25	9.9000	10.0000	10.1000
-17	71.524	73.704	75.943	26	9.4926	9.5924	9.6924
-16	67.819	69.848	71.932	27	9.1042	9.2038	9.3035
-15	64.328	66.218	68.156	28	8.7338	8.8330	8.9324
-14	61.037	62.797	64.601	29	8.3806	8.4792	8.5782
-13	57.934	59.573	61.252	30	8.0436	8.1416	8.2399
-12	55.007	56.534	58.097	31	7.7220	7.8193	7.9169
-11	52.246	53.668	55.123	32	7.4151	7.5115	7.6083
-10	49.639	50.963	52.318	33	7.1220	7.2175	7.3134
-9	47.177	48.411	49.672	34	6.8421	6.9366	7.0316
-8	44.852	46.001	47.176	35	6.5747	6.6681	6.7622
-7	42.654	43.725	44.819	36	6.3193	6.4115	6.5045
-6	40.577	41.575	42.593	37	6.0751	6.1662	6.2581
-5	38.613	39.543	40.491	38	5.8417	5.9316	6.0223
-4	36.755	37.621	38.504	39	5.6185	5.7071	5.7966
-3	34.997	35.804	36.626	40	5.4050	5.4924	5.5806
-2	33.333	34.085	34.851	41	5.2007	5.2868	5.3739
-1	31.757	32.458	33.171	42	5.0053	5.0901	5.1758
0	30.265	30.918	31.581	43	4.8182	4.9017	4.9861
1	28.840	29.448	30.065	44	4.6391	4.7213	4.8044
2	27.491	28.056	28.631	45	4.4676	4.5484	4.6303



R-T表

广东爱晟电子科技有限公司

R25	10(KΩ)	阻值精度	1.0%	型号: DT103F3743A			
B25/50	3743K	B值精度	1.0%				
Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)	Temp(°C)	Rmin(KΩ)	Rnor(KΩ)	Rmax(KΩ)
46	4.3034	4.3828	4.4633	89	1.0056	1.0390	1.0734
47	4.1460	4.2241	4.3033	90	0.9748	1.0075	1.0412
48	3.9952	4.0720	4.1498	91	0.9451	0.9772	1.0101
49	3.8507	3.9261	4.0026	92	0.9165	0.9478	0.9801
50	3.7121	3.7862	3.8614	93	0.8888	0.9194	0.9510
51	3.5788	3.6516	3.7254	94	0.8620	0.8920	0.9230
52	3.4510	3.5224	3.5950	95	0.8361	0.8655	0.8958
53	3.3284	3.3985	3.4697	96	0.8111	0.8399	0.8696
54	3.2107	3.2795	3.3494	97	0.7870	0.8151	0.8442
55	3.0977	3.1652	3.2339	98	0.7636	0.7912	0.8196
56	2.9893	3.0555	3.1229	99	0.7410	0.7680	0.7958
57	2.8852	2.9501	3.0162	100	0.7192	0.7456	0.7729
58	2.7852	2.8488	2.9137	101	0.6981	0.7239	0.7506
59	2.6891	2.7515	2.8152	102	0.6777	0.7029	0.7291
60	2.5968	2.6580	2.7204	103	0.6579	0.6827	0.7082
61	2.5081	2.5681	2.6293	104	0.6388	0.6630	0.6881
62	2.4229	2.4817	2.5417	105	0.6203	0.6440	0.6685
63	2.3410	2.3986	2.4574	106	0.6024	0.6256	0.6496
64	2.2622	2.3187	2.3763	107	0.5851	0.6078	0.6313
65	2.1864	2.2418	2.2983	108	0.5684	0.5906	0.6136
66	2.1135	2.1678	2.2232	109	0.5521	0.5739	0.5964
67	2.0434	2.0966	2.1509	110	0.5364	0.5577	0.5798
68	1.9760	2.0280	2.0812	111	0.5212	0.5421	0.5637
69	1.9110	1.9620	2.0142	112	0.5065	0.5269	0.5481
70	1.8485	1.8985	1.9496	113	0.4923	0.5122	0.5330
71	1.7884	1.8373	1.8874	114	0.4784	0.4980	0.5183
72	1.7304	1.7784	1.8274	115	0.4651	0.4842	0.5041
73	1.6746	1.7216	1.7696	116	0.4521	0.4708	0.4903
74	1.6209	1.6669	1.7140	117	0.4396	0.4579	0.4770
75	1.5691	1.6141	1.6603	118	0.4274	0.4453	0.4640
76	1.5192	1.5633	1.6085	119	0.4156	0.4332	0.4515
77	1.4711	1.5143	1.5586	120	0.4042	0.4214	0.4393
78	1.4248	1.4671	1.5104	121	0.3931	0.4099	0.4275
79	1.3801	1.4215	1.4640	122	0.3824	0.3989	0.4160
80	1.3370	1.3775	1.4192	123	0.3719	0.3881	0.4049
81	1.2947	1.3344	1.3751	124	0.3618	0.3777	0.3942
82	1.2539	1.2927	1.3326	125	0.3521	0.3676	0.3837
83	1.2145	1.2525	1.2916	126	0.3426	0.3577	0.3736
84	1.1765	1.2137	1.2520	127	0.3334	0.3482	0.3637
85	1.1399	1.1763	1.2138	128	0.3244	0.3390	0.3542
86	1.1045	1.1402	1.1768	129	0.3158	0.3300	0.3449
87	1.0704	1.1052	1.1412	130	0.3074	0.3213	0.3359
88	1.0374	1.0715	1.1067	131	0.2992	0.3129	0.3271

